

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1-2. (Canceled)

3. (Currently Amended) A liquid crystal panel driving method for a liquid crystal panel having a liquid crystal between a pair of electrodes in which optical characteristics of the liquid crystal are changed by applying a driving signal between the pair of electrodes, the liquid crystal panel driving method comprising:

sensing a temperature of at least one of the liquid crystal panel and an environment in which the liquid crystal panel is disposed; and

applying a low frequency signal as the driving signal in case that the sensed temperature is low, the low frequency signal having a frequency lower than a frequency of a driving signal used in case that the sensed temperature is normal, and varying a frequency of the driving signal discontinuously with respect to the sensed temperature to exclude a ~~predetermined frequency~~; an integral multiple of a frequency of a commercial power supply.

4. (Original) The liquid crystal panel driving method according to claim 3, further comprising varying a frame frequency obtained when performing time-division driving a plurality of pixels arranged in a matrix form on the liquid crystal panel, based on the sensed temperature, so that at least a frequency corresponding to an integer multiple of 50 Hz is avoided.

5. (Original) The liquid crystal panel driving method according to claim 3, further comprising varying a frame frequency obtained when performing time-divisional driving of a plurality of pixels arranged in a matrix form on the liquid crystal panel, based on the sensed temperature, so that at least a frequency corresponding to an integer multiple of 60 Hz is avoided.

6. (Currently Amended) The liquid crystal panel driving method according to claim 3, further comprising ~~A liquid crystal panel driving method for a liquid crystal panel having a liquid crystal between a pair of electrodes in which optical characteristics of the liquid crystal are changed by applying a driving signal between the pair of electrodes, the liquid crystal panel driving method comprising:~~

~~—————sensing a temperature of at least one of the liquid crystal panel and an environment in which the liquid crystal panel is disposed; and~~

~~—————applying a low frequency signal as the driving signal in case that the sensed temperature is low, the low frequency signal having a frequency lower than a frequency of a driving signal used in case that the sensed temperature is normal, and setting a driving frequency of each pixel of the liquid crystal panel so that, when the temperature is -20 °C, each pixel is driven at a frequency not greater than 1.28 kHz, and, when the temperature is +25 °C, each pixel is driven at a frequency not greater than 2.56 kHz.~~

7. (Original) The liquid crystal panel driving method according to claim 6, further comprising setting the driving frequency of each pixel of the liquid crystal panel so that, when the temperature is +70 °C, each pixel is driven at a frequency not greater than 4.16 kHz.

8. (Currently Amended) The liquid crystal panel driving method according to claim 3, further comprising ~~A liquid crystal panel driving method for a liquid crystal panel having a liquid crystal between a pair of electrodes in which optical characteristics of the liquid crystal are changed by applying a driving signal between the pair of electrodes, the liquid crystal panel driving method comprising:~~

~~—————sensing a temperature of at least one of the liquid crystal panel and an environment in which the liquid crystal panel is disposed; and~~

~~—————applying a low frequency signal as the driving signal in case that the sensed temperature is low, the low frequency signal having a frequency lower than a frequency of a~~

~~driving signal used in case that the sensed temperature is normal,~~ setting a frame frequency to not greater than 40 Hz when the temperature is within a range including -20 °C, and setting the frame frequency in the range of 70 Hz to 90 Hz when the temperature is within a range including +25 °C.

9-10. (Canceled)

11. (Currently Amended) A liquid crystal device comprising a liquid crystal panel having a liquid crystal between a pair of substrates and a driving circuit that applies a driving signal between the pair of substrates and that varies optical characteristics of the liquid crystal, the liquid crystal device further comprising:

a temperature sensor that senses a temperature of at least one of the liquid crystal panel and an environment in which the liquid crystal panel is disposed; and a temperature compensating device that applies a low frequency signal as the driving signal in case that the sensed temperature is low, the low frequency signal having a frequency lower than a frequency of a driving signal used in case that the sensed temperature is normal, the temperature compensating device discontinuously varying a frequency of the driving signal with respect to the sensed temperature to ~~exclude a predetermined frequency.~~ an integral multiple of a frequency of a commercial power supply.

12. (Currently Amended) The liquid crystal device according to claim 11, wherein the temperature compensating device ~~varying~~ varies a frame frequency obtained when performing time-division driving of a plurality of pixels arranged in a matrix form on the liquid crystal panel, based on the sensed temperature, so that at least a frequency corresponding to an integer multiple of 50 Hz is avoided.

13. (Currently Amended) The liquid crystal device according to claim 11, wherein the temperature compensating device ~~varying~~ varies a frame frequency obtained when performing time-division driving of a plurality of pixels arranged in a matrix form on the

liquid crystal panel, based on the sensed temperature, so that at least a frequency corresponding to an integer multiple of 60 Hz is avoided.

14. (Currently Amended) The liquid crystal device according to claim 13, when varying the frame frequency while avoiding a specific frequency, the temperature compensating device ~~varying~~ varies the frame frequency in a hysteretic manner.

15. (Original) The liquid crystal device according to claim 14, the temperature compensating device avoiding a specific frequency and varying the frame frequency in accordance with the sensed temperature by varying the frame frequency in a stepwise manner.

16. (Original) The liquid crystal device according to claim 15, the temperature compensating device continuously varying the frame frequency in accordance with the sensed temperature except when the frame frequency is varied while avoiding a specific frequency.

17. (Currently Amended) The liquid crystal device according to claim 11, wherein
~~A liquid crystal device comprising a liquid crystal panel having a liquid crystal between a pair of substrates and a driving circuit that applies a driving signal between the pair of substrates and that varies optical characteristics of the liquid crystal, the liquid crystal device further comprising:~~

~~a temperature sensor that senses a temperature of at least one of the liquid crystal panel and an environment in which the liquid crystal panel is disposed; and a temperature compensating device that applies a low frequency signal as the driving signal in case that the sensed temperature is low, the low frequency signal having a frequency lower than a frequency of a driving signal used in case that the sensed temperature is normal, the temperature compensating device setting~~ sets ~~a driving frequency of each pixel of the liquid crystal panel to not greater than 1.28 kHz when the temperature is -20 °C and to not greater than 2.56 kHz when the temperature is +25 °C.~~

18. (Original) The liquid crystal device according to claim 17, the temperature compensating device setting the driving frequency of each pixel of the liquid crystal panel to not greater than 4.16 kHz when the temperature is +70 °C.

19. (Currently Amended) The liquid crystal device according to claim 11, wherein
~~A liquid crystal device comprising a liquid crystal panel having a liquid crystal between a pair of substrates and a driving circuit that applies a driving signal between the pair of substrates and that varies optical characteristics of the liquid crystal, the liquid crystal device further comprising:~~

~~a temperature sensor that senses a temperature of at least one of the liquid crystal panel and an environment in which the liquid crystal panel is disposed; and a temperature compensating device that applies a low frequency signal as the driving signal in case that the sensed temperature is low, the low frequency signal having a frequency lower than a frequency of a driving signal used in case that the sensed temperature is normal, the temperature compensating device setting-sets the frame frequency to not greater than 40 Hz when the temperature is -20 °C, setting-sets the frame frequency in the range of 70 Hz to 90 Hz when the temperature is +25 °C, and setting-sets the frame frequency to not less than 130 Hz when the temperature is +70 °C.~~

20. (Currently Amended) The liquid crystal device according to claim 17, wherein
the temperature compensating device is a synchronizing signal frequency varying device that varies a frequency of the driving signal by varying a frequency of a synchronizing signal applied to a liquid crystal drive control circuit for controlling the driving circuit based on the sensed temperature.

21. (Previously Presented) The liquid crystal device according to claim 17, the temperature sensor being a thermistor formed together with the driving circuit in a semiconductor device.

22. (Previously Presented) An electronic apparatus comprising the liquid crystal device as set forth in claim 21 as a display device.

23. (Previously Presented) The liquid crystal panel driving method according to claim 6, each pixel being driven at a frequency not less than 0.256 kHz when the temperature is at +25 °C and at a frequency not less than 0.1 kHz when the temperature is at -20 °C.

24. (Previously Presented) The liquid crystal panel driving method according to claim 8, the frame frequency being set to not less than 130 Hz when the temperature is at +70 °C.

25. (Canceled)

26. (Previously Presented) The liquid crystal panel driving method according to claim 3, varying the frequency of the driving signal including continuously varying the signal at frequencies higher than, and lower than, the excluded predetermined frequency.

27. (Canceled)

28. (Currently Amended) The liquid crystal device according to claim 11, wherein varying the frequency of the driving signal ~~including~~ includes continuously varying the signal at frequencies higher than, and lower than, the excluded predetermined frequency.

29. (New) The method according to claim 3, wherein the frequency of the commercial power supply is 50 Hz.

30. (New) The method according to claim 3, wherein the frequency of the commercial power supply is 60 Hz.

31. (New) The liquid crystal device according to claim 11, wherein the frequency of the commercial power supply is 50 Hz.

32. (New) The liquid crystal device according to claim 11, wherein the frequency of the commercial power supply is 60 Hz.